





# SPEAKER MODEL :79SP-2

## DESCRIPTION SPEAKER



## SPEAKER SPECIFICATION

|                                   |                            |            |   |
|-----------------------------------|----------------------------|------------|---|
| Outer Dimensions                  | 78mm(See attached drawing) |            |   |
| Rated (Max.)Input                 | 10 W (12W)                 |            |   |
| Voice Coil Imp.                   | 8 ± 1.2                    | Ω          | ( 400 Hz 1 V )                            |
| Lowest Resonance Frequency ( fo ) | 95 ± 19                    | Hz         | ( 1 V )                                   |
| Sound Pressure Level              | 91 ± 2                     | dB         | ( 0.1 w 0.5 m ) at(0.6)(0.8)(1.0)(1.2)KHZ |
| Frequency Response Deviation      | FO Hz ~                    | 20 KHz max | -10 dB                                    |
| Operating temperature             | -20 +50 ± 2                | °C         | Hours 2 0 ~ 5 0 % R.H.                    |
| Load test                         | White noise at             | 10 W       | 48 hours                                  |
| Weight                            | 293 g                      |            |   |

Other non-stipulated matters are based on CNS4784 4785 4786 based on JIS.C. 5530 5531

## FREQUENCY RESPONSE CURVE<sup>(7\*18)</sup>

